

Smoke Alarm

Model Ei 100R Ionisation

- High sensitivity – responds to all standard fires
- Dual Ionisation chamber - quick response fast flaming fires
- Supply voltage 10.2 to 14 volts
- Interconnect up to 12 alarms
- Relay contacts
- Built in sounder
- Test button
- Kitemarked to BS5446 -1:2000
- 5 year guarantee



Product Description

The Ei100R is an Ionisation Smoke Alarm that is designed to operate with suitable 12 volt control panels and to provide a loud local alarm.

Ionisation smoke alarms operate on the principle that electrical current flowing between electrodes in an ionization chamber is reduced when smoke particles enter.

Ionisation technology gives a rapid response to fast flaming fires

Relay contacts (normally open and closed supplied) are available for triggering the panel itself and its associated ancillary products, such as extra loud sirens, magnetic door holders, etc.

The alarms can be interconnected so that when one alarm senses fire, all the units located throughout the premises sound.

The Ei100R is easily installed and comes supplied with all necessary screw fixings.

Operation

- The smoke detector will activate the built in sounder upon sensing smoke particles
- The smoke detector will automatically reset itself and silence the sounder when smoke particles are no longer present in the sensing chamber
- The built in sounder will provide a minimum sound output of 85dB at 3m
- The "Test" button will perform a self test and sound the horn (it may take up to 10 seconds)
- Red LED –flashes every 40 seconds to indicate unit checks
- Interconnect up to 12 other alarms (9V ionisation, optical or heat) when one senses smoke, all alarm. Helps ensure warning will be heard throughout the house

Sparks Electrical Wholesalers Ltd

659-661 Holloway Road
London N19 5SE
Tel: 020 7263 8007
www.sparksdirect.co.uk

Model Ei100R Ionisation

Technical Specification

Sensor	Ionisation, uses electrically charged ions that will react to smoke particles	Alarm:	Piezoelectric-horn in unit
Sensitivity:	Complies with BS 5446 Part 1: 2000	Alarm Sound Output:	85dB (minimum) at 3m
Source:	Americium 241	Temperature Range:	0 to 40°C
Airspeed:	Essentially immune to the effect of airspeed.	Humidity Range:	0% to 90% Relative Humidity
Button Test:	Simulates the effect of smoke and checks chamber, electronics and horn.	Fixing:	Screw fixings supplied
Supply Voltage:	10.2 to 14 volts	Plastic material:	UL94HB flame retardant
		Dimensions:	140x120x45 mm
		Weight:	150 gram
		Warranty:	5 year (limited) warranty
		Approvals:	Kitemarked to BS5446-1:2000, CE Approved

Specifications are subject to change

Installation & Placement



Alarms should be placed in accordance with the general guidelines shown in the diagram above. These recommendations are based on the problem of areas of "dead air" close to corners of rooms and apexes of ceilings, which could result in the prevention of smoke reaching the smoke detector

Please consult the Instruction Leaflet supplied with the Ei100R for detailed instructions as to how to correctly install and position the smoke detector

Important Precaution:

Do not install the actual smoke/heat alarm itself in new or renovated buildings until all work is completed (including floor coverings) and the building has been fully cleaned. (Excessive dust and debris from building work can contaminate the smoke chamber and cause problems, and it will also invalidate the guarantee). If it must be installed, cover it completely, particularly around the edges, with a dust cover (eg. a plastic bag), until all cleaning is finished..

Sparks Electrical Wholesalers Ltd

659-661 Holloway Road
London N19 5SE
Tel: 020 7263 8007
www.sparksdirect.co.uk