



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Painted Silver	<b>CABLE LENGTH:</b>	Not Applicable
<b>MAIN MATERIAL:</b>	Metal - Aluminium	<b>GROSS WEIGHT:</b>	0.34 (kg)
<b>DIMENSIONS:</b>	Ø:60mm D: 90mm	<b>CLASS:</b>	CE (Class III)
<b>INSTALLATION ORIENTATION:</b>	Ground/Floor/Wall Mount	<b>IP RATING:</b>	IP67
<b>CUT OUT HOLE:</b>	40mm/1-9/16"	<b>BATHROOM ZONE:</b>	Zones 1, 2, 3
<b>RECESS DEPTH:</b>	90mm/3.54"	<b>VOLTAGE:</b>	Constant Current 700mA
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Suitable for mounting on flammable materials

### LAMP

<b>LIGHT SOURCE:</b>	High Power LED	<b>MACADAM ELIPSE:</b>	To Be Advised
<b>MAXIMUM WATTAGE:</b>	3W Max	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	Not Applicable
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>LUMINOUS FLUX:</b>	11 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOUR TEMP:</b>	3000 (K)	<b>AVERAGE LIFESPAN:</b>	60,500 (hrs)
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	To Be Advised		


### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER/BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Control Gear Dependent	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	To Be Advised
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER/BALLAST INCLUDED?</b>	No

## ADDITIONAL INFORMATION



 1000 HOURS SALT-SPRAY TESTED



BOX QUANTITY X 50

# PRODUCT ELEVATIONS

---

