

# VETRO SQUARE FIRE-RATED 5732

SKU 1254008

astro



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Black	<b>CABLE LENGTH:</b>	Not Applicable
<b>MAIN MATERIAL:</b>	Glass - Float	<b>GROSS WEIGHT:</b>	0.732 (Kg)
<b>DIMENSIONS:</b>	H: 90mm W: 90mm D: 94mm	<b>CLASS:</b>	CE (Class III)
<b>INSTALLATION ORIENTATION:</b>	Ceiling Mount	<b>IP RATING:</b>	IP65
<b>CUT OUT HOLE:</b>	76mm/3in	<b>BATHROOM ZONE:</b>	Zone 1, 2, 3
<b>RECESS DEPTH:</b>	124mm	<b>VOLTAGE:</b>	Constant Current 350 (mA)
<b>FIRE RATING:</b>	90 min	<b>PRODUCT F MARK:</b>	Not Applicable

### LAMP

<b>LIGHT SOURCE:</b>	COB LED	<b>MACADAM ELIPSE:</b>	2-Step
<b>MAXIMUM WATTAGE:</b>	6W	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	20.4 (Degrees)
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>LUMINOUS FLUX:</b>	614.3 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOUR TEMP:</b>	2700 (K)	<b>AVERAGE LIFESPAN:</b>	36,300 (Hrs)
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	14		

### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER/BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Control Gear Dependant	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	49.74 (lm/W)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER/BALLAST INCLUDED?</b>	No

## ADDITIONAL INFORMATION



BOX QUANTITY X12

PRODUCT ELEVATIONS

