

DATASHEET




CFR5WW / CFR5CW


230V IP65 5W

Fire-Rated LED Downlight

www.mlaccessories.co.uk



MLA PART CODE	CFR5WW	CFR5CW
DESCRIPTION	230V IP65 Fire-Rated LED Downlight	
FINISH	White	
NETT WEIGHT (Kg)	0.18	
DIMENSIONS (mm)	Diameter – 84 Recessed depth – 50 Projection – 4	
CUT-OUT (mm)	55	
MINIMUM VOID SPACE (mm)	100	
WATTAGE (W)	5	
LUMENS (lm)	570 ±5%	
EFFICACY (lm/W)	105	
CCT	3000K	4000K
LED COLOUR	Warm white	Cool white
CRI	>80	
RUNNING CURRENT (A)	0.028	
POWER FACTOR	0.86	0.85
BEAM ANGLE	60°	
LIFE SPAN (Hrs)	50,000	
INPUT VOLTAGE	Mains 230V 50Hz	
CONSTRUCTION	Pressed steel	
CLASS	Class II, with non-functional earth	
IP RATING	IP65	
DIMMABLE	Yes, with most trailing edge dimmers	
WARRANTY	3 Years	
ORIGIN OF MANUFACTURE	China	
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes	
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598	
EAN	5056270802931	5056270802955



AVNOV19_V1