

DL6799 - CombiVolt™ 5

TrueRMS Voltage, Continuity & Current Tester

The NEW CombiVolt 5 is a five-in-one tester with a rugged, ergonomically formed housing for perfect handling. With a range of testing function including TRMS AC/DC voltages, TRMS AC/DC current, Non-Contact & Single Pole Voltage detection with a multitude of other functions, the CombiVolt 5 offers complete versatility to the Electrical Engineer.

Fully conformant to EN 61010-1, 61010-2-032, 61010-2-33, 61010-031
61326-1 & 61326-2-2 and the safety standards of CAT II 1kV & CAT III 600V

Features

- Meets safety and performance requirements of BS EN 61010-1
- 750V TRMS AC / 1000V DC voltage measurement
- Non Contact & Single Pole Voltage Detection
- 200A TRMS AC /DC Current measurement
- 60M Ohm Resistance with Audible Continuity
- Audible Continuity
- Capacitance
- Carry Case
- GS38 shrouded probe tips
- Bright LED Flashlight
- Carry Case

Specifications

Voltage	
AC Voltage(TrueRMS)	0 - 750V
Typical Accuracy	+/- 1.2% + 3 digits
Frequency	45 - 400Hz
DC Voltage	0 - 1000V
Typical Accuracy	+/- 0.8% + 3 digits
Single Pole Indication	
>100Vrms	
Non-Contact Voltage Detection	
>100Vrms	Distance <10mm
Current	
AC Current	200A
Typical Accuracy	+/- 2.5% + 5 digits
Frequency	50 - 60Hz
DC Current	200A
Typical Accuracy	+/- 2.5% + 5 digits
Continuity	
Measuring range	0 - 600 Ohms Audible <100 Ohms
Resistance	
Measuring range	0.1 - 60MΩ
Typical Accuracy	+/- 1.0% + 2 digits
Capacitance	
Measuring range	60.00nF to 60.00mF
Diode	
Measuring range	6.000V
Other Information	
Power supply	2 x 1.5 V LR06 (AA) batteries
Dimensions	210 x 53 x 35 mm
Weight	164g (battery included)

