

**Invicta 3 125A TP&N
Distribution Boards**
Surface mounted steel
enclosures.

Enclosure degree of protection:
IP3X

Enclosures are available with
plain or glazed doors.

Fully shrouded copper busbar,
rated 25kA short circuit
conditional current.

Supplied without incoming and
outgoing devices.

A hager incoming kit must be
used.

Complies with BS EN 60439-3.

For dimensions see page 3.25.

Invicta 3 (125A Incoming 63A Outgoing)



JK106BG

Description	Cat ref. Plain door	Cat ref. Glazed door
4 Triple Pole Ways	JK104B ¹	JK104BG ¹
6 Triple Pole Ways	JK106B ¹	JK106BG ¹
8 Triple Pole Ways	JK108B	JK108BG
12 Triple Pole Ways	JK112B	JK112BG
16 Triple Pole Ways	JK116B	JK116BG
18 Triple Pole Ways	JK118B	JK118BG
24 Triple Pole Ways	JK124B	JK124BG

¹ If additional cable space is required when fitting a meter pack
a 300mm JK101SE can be used, see page 3.19.



JK11003S

125A Incomer Kits (note: these incomer kits will only fit the 125A board(s))

Description	Cat ref.
3 Pole 100A Switch Disconnecter Incomer Kit (fits within distribution board)	JK11003S
4 Pole 100A Switch Disconnecter Incomer Kit (fits within distribution board)	JK11004S
3 Pole 125A Switch Disconnecter Incomer Kit (fits within distribution board)	JK11253S
4 Pole 63A Contactor Incomer Kit includes Switch Disconnecter (fits below distribution board, 300mm high)	JK10634C ²
4 Pole 100A Contactor Incomer Kit includes Switch Disconnecter (fits below distribution board, 450mm high)	JK11004C ²
125A Direct Connection Kit (fits within distribution board)	JK11254D
4 Pole 63A 30mA RCCB Incomer Kit (fits within distribution board)	JK10634RH
4 Pole 100A 30mA RCCB Incomer Kit (fits within distribution board)	JK11004RH
4 Pole 100A 300mA RCCB Incomer Kit (fits within distribution board)	JK11004RL
4 Pole 100A 300mA Time Delayed RCCB Incomer Kit (fits within distribution board)	JK11004RLD
4 Pole 100A 100mA RCCB Incomer Kit (fits within distribution board)	JK11004RM
4 Pole 100A 100mA Time Delayed RCCB Incomer Kit (fits within distribution board)	JK11004RMD

² A 300 / 450mm space is required below the board for fitting, see page 3.26 for dimensions.

**MCB
Type B, C & D 10kA & 15kA Single and Triple Pole**

For a full list of protection devices
see section 4.

Cat ref.		0.5A	1A	2A	3A	4A	6A	10A	16A	20A
B Curve	Single Pole	-	-	-	-	-	NBN106A	NBN110A	NBN116A	NBN120A
	Triple Pole	-	-	-	-	-	NBN306A	NBN310A	NBN316A	NBN320A
C Curve	Single Pole	NCN100A	NCN101A	NCN102A	NCN103A	NCN104A	NCN106A	NCN110A	NCN116A	NCN120A
	Triple Pole	NCN300A	NCN301A	NCN302A	NCN303A	NCN304A	NCN306A	NCN310A	NCN316A	NCN320A
D Curve	Single Pole	NDN100A	NDN101A	NDN102A	NDN103A	NDN104A	NDN106A	NDN110A	NDN116A	NDN120A
	Triple Pole	NDN300A	NDN301A	NDN302A	NDN303A	NDN304A	NDN306A	NDN310A	NDN316A	NDN320A