

DOWNLIGHTS  
RAMADA IP65 FIRE RATED DOWNLIGHTS

**ROBUS®**

This attractive looking dimmable Fire and IP65 rated downlight uses, high quality components and materials to provide an exceptionally versatile long-life downlight solution for Domestic or Commercial installations. It replaces inefficient traditional Halogen or Compact Fluorescent light sources to make huge energy cost savings to reduce carbon emissions



**Applications:**

- Domestic dining, living, bathroom and bedroom spaces
- Hotel & Office reception areas
- Shops and other retail premises
- Pubs, clubs and restaurants
- Complimentary lighting in meeting or function rooms

**Construction:**

- White powder coated die-cast aluminium trim
- Die-cast aluminium body
- Clear toughened glass cover
- Pressed steel insulation stand-off
- Spring steel ceiling fixing springs

**Features:**

- White powder coated die-cast aluminium trim as standard, complete with brushed chrome clip on trim accessory
- Optional polished chrome clip-on trim - RRATRIM-03
- Die-cast Aluminium body
- Available in 3,000K or 4,000K options
- High quality single LED and driver technology provide:
  - Comparable light output to 50W LV Halogen
  - Low power consumption of only 8.5 watts
  - Cool running
  - Long life
- Solid state technology
- Integral driver compatible with many leading/trailing edge dimmers
- 60 degree LEDchroic optic
- Integrated insulation stand-off
- 130mm 2 core flex to remote, large terminal connector block
- Independently tested for compliance with parts B, C & E of Building Regulations
- Ingress Protection of IP65


**Benefits:**

- Quality materials provide great aesthetics and alternative colour finish to match or contrast with décor, door, or other furniture
- Ideal for matching to polished chrome bathroom fittings
- Conducts heat away from LED's and driver to ensure cool running and long life
- Provides a warm or neutral white light colour choice depending on use of the lit space
- Provides a one for one replacement for LV Halogen, particularly useful as retro-fit where all cut-outs can be utilised
- Compared to many lower performing LED alternatives available reduces the number of fittings and therefore the solution cost
- Wide ambient operating temperature range for hot environments
- No maintenance costs or inconvenient lamp failures in commercial, entertainment or retail installations
- Suitable for switching by most sensor or control systems, with long or short time delays, without detriment to life time
- Life is not affected by on/off heating/cooling cycles as are many traditional light sources
- Provides selectable light levels suitable for task or subtle lighting
- Driver location choice is not an issue
- Wide, uniform light beam provides the star-like twinkle of Halogen without bright or dark rings and patches often associated with it
- Allows mineral insulation to be loosely laid over the fitting to reduce cold spots in the void space without overheating issues
- Allows for 1.5mm<sup>2</sup> solid or stranded, loop in/out termination
- Retains the integrity of traditional 30, 60 & 90-minute fire rated ceiling and floor joist combinations
- Complies with regulatory acoustic and air-flow requirements
- The same fitting is suitable for installation in most areas of a property to provide a common aesthetic

DOWNLIGHTS  
RAMADA IP65 FIRE RATED DOWNLIGHTS

**ROBUS**<sup>®</sup>

Product Code:	RRA083060-01	RRA084060-01
Comparable to Halogen (W):	50	50
Total Power (W):	8.5	8.7
Total Light Output (lm):	590	670
Efficacy (lm / cctW):	69	77
Rated Life (hrs):	30,000	30,000
Warranty (yrs):	2	2
Illuminance at 1m (lux):	540	640
Beam Angle (deg):	60	60
CCT (K):	3,000	4,000
CRI (Ra):	80	80
Ingress Protection (IP):	65	65
Operating Temperature (°C):	-20 < Ta < +40	-20 < Ta < +40
Operating Voltage (Vac):	220-240	220-240
Power Factor (PF):	0.9	0.9
Cut Out (mm):	70	70
Height (mm):	94	94
Diameter (mm):	86	86
Box Qty:	1	1
Weight (kg):	0.3	0.3



**Accessories:**

White and Brushed Chrome trims **Included**  
Optional Polished Chrome clip-on trim **RRATRIM-03**

**Standards & Approvals:**

Complies with: EN 60598-1, EN 60598-2-2, EN 62471, EN 62493, EN 55015, EN 61000-3-2, EN 61000-3-3, BS 476-21, EN 61374-1, EN 61374-2-13, EN61547, EN62031

**Cone Illuminance Diagram:**




Diagram for RRA083060-01. Other diagrams available on request



**Polar Intensity Diagram:**




Diagram for RRA083060-01. Other diagrams available on request



PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000 WEB: WWW.LEDGROUPROBUS.COM  
AUS: TEL: +61 7 3890 5444 WEB: WWW.LEDGROUPROBUS.COM.AU