


## Primed White (Paintable) Range - Primed White

Shaver Socket Output Voltage 110/240V - PW.285.W



Range	Primed White (Paintable) Range	
Product	Primed White Flat Plate PW	
Insert Type	Shaver Socket Output Voltage 110/240V	
Plate Finish	Primed White	
Switch Colour	-	
Body and Switch Trim	White	
Height	147 mm	
Width	86 mm	
Fixing Hole Centres	Box Fixing = 120.6 mm	
Minimum Box Depth	55	
Current -		
Voltage 230 V		
Power -		
Terminal Capacity	acity 4 mm2	
Earth Terminal Capacity	5 mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5°C - 40°C	
Recommended Location	Indoor use only	
Standard	BS EN 61558-2-5	

British o	ucts listed conform to current in European standards and the information is correct at the time to press.	All accessories are manufactured under an accredited BS EN 9001:2008 Quality System.	It is the policy of the company to continually improve products as part of our development program.  Therefore, we respect the right to alter designs and dimensions without prior notice.
within th	ons and diagrams are produced e limitations of reproductions ting processes are not binding.	Due to manufacturing process we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as 05.07.2022. E&OE



British Standards
The Heritage Brass Electrical
Collection is designed Collection is designed and manufactured to comply with the requirements of the relevant British Standards.





M. Marcus Ltd. Telephone: +44 (0)1384 247 845 Fax: 01384 243 312 Email: electsales@m-marcus.com m.marcus Website: www.m-marcus.com