


Primed White (Paintable) Range - Primed White

1 Gang LED Dimmer - PW.560.TED



Dense	Drimod Mhite (Deintehle) Denge	
Range		
Product	Primed White Flat Plate PW	
Insert Type	1 Gang LED Dimmer	
Plate Finish	Primed White	
Switch Colour	White	
Body and Switch Trim	White	
Height	86 mm	
Width	86 mm	
Fixing Hole Centres	Box Fixing = 60.3 mm	
Minimum Box Depth	35	
Current	-	
Voltage	230 V	
Power	Max 120 W - 10 Lamps Trailing Edge	
Terminal Capacity	4 mm2	
Earth Terminal Capacity	5 mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5°C - 40°C	
Recommended Location	Indoor use only	
Standard	BS EN 55014, BS EN 60669-2-1	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN 9001:2008 Quality System.	It is the policy of the company to continually improve products as part of our development program. Therefore, we respect the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are produced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing process we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as 05.07.2022. E&OE



British Standards The Heritage Brass Bectrical Collection is designed and manufactured to comply with the requirements of the relevant British Standards.



M. Marcus Ltd. Telephone: +44 (0)1384 247 845 Fax 01384 243 312 Email: electsales@m-marcus.com m.marcus Website: www.m-marcus.com