Aura Shower Kit

Shower ventilation



Key Features

- **Axial in-line fan**
- **Ventilation up to 108 m³/hr**
- **Designed for ventilation / lighting above shower cubicles**
- **Use for both supply or extraction**
- **Compact and quiet in operation**
- **Mounting bracket included**
- **Ductable**
- **Halogen lamp option**
- **IPX4 rating**
- **3 year warranty**

BASIC SWITCHING TIMER

Aura Shower Kit range

Highly reliable fan in a modular design for ease of installation and maintenance. Aura In-Line Fans are designed to provide extraction levels that comply with the latest Building Regulations.

The fans are manually operated by a remote switch (switch not supplied). Timer control versions are also available. Install in-line with ducting for a quiet and discreet installation.

The Aura in-line fan comes with a fixing bracket and is compact, attractively styled and ductable over short lengths. They are the ideal solution for removing damp moist air, odours and airborne pollutants from toilets and bathrooms.

ALWAYS PULL FLEXIBLE DUCTING TAUGHT TO ENSURE INSTALLED PERFORMANCE AIR FLOW.





Models

Basic	Control by Remote Switch
Timer	Timer can be set to run on between 2 and 30 minutes



Contents of Kits


9041420	Aura 100B, 3m flex duct, ties, extract valve, external grille
9041419	Aura 100T, 3m flex duct, ties, extract valve, external grille
9041422	Aura 100B, 3m flex duct, ties, halogen lamp + chrome and white grilles, external grille
9041421	Aura 100T, 3m flex duct, ties, halogen lamp + chrome and white grilles, external grille

Technical Data

Specification	Aura Shower Kit	Aura T Shower Kit	Aura Shower Kit with Hallogen Lamp	Aura T Shower Kit with Hallogen Lamp
Air flow m^3/hr* / l/sec*	108 / 30	108 / 30	108 / 30	108 / 30
Fan type	Axial	Axial	Axial	Axial
Controls	Basic	Timer (adjustable)	Basic	Timer (adjustable)
Mounting	In-Line	In-Line	In-Line	In-Line
Sound pressure dB(A)@3m	39	39	39	39
Power watts	16	16	16	16
Amps	0.01	0.01	0.01	0.01
Specific Fan Power (SFP)	0.53	0.53	0.53	0.53
Duct diameter (mm)	100	100	100	100
Voltage	230v / 1ph / 50Hz	230v / 1ph / 50Hz	230v / 1ph / 50Hz	230v / 1ph / 50Hz
Rating	IPX4	IPX4	IPX4	IPX4
Material finish	ABS	ABS	ABS	ABS
Weight (kg)	0.41	0.41	0.41	0.41
Dimensions (H x W x D) mm	110 x 160 x 113	110 x 160 x 113	110 x 160 x 113	110 x 160 x 113
Part No.	**9041420**	**9041419**	**9041422**	**9041421**


* Air flow at free discharge

Dimensions (mm)



Model	A	B	C	D
Aura shower kit	110	113	160	144

Performance



Controls and Accessories

A range of accessories including flexible and rigid ducting kits, controls and grilles are available.

Call: 01494 560800 **Visit: airflow.com**

Airflow Developments Limited
Aidelle House, Lancaster Road,
Cressex Business Park,
High Wycombe, Buckinghamshire,
United Kingdom, HP12 3QP

E-mail: info@airflow.com
Telephone: +44 (0) 1494 525252
Facsimile: +44 (0) 1494 461073

airflow.com

© Airflow Developments Limited. Airflow Developments Limited reserve the right, in the interests of continuous development, to alter specifications without prior notice. All orders are accepted subject to our conditions of sale which are available on request