

DATASHEET



EMPOWER2

**230V IP20 3W LED Emergency Downlight 6000K
(maintained/non-maintained use)**

www.mlaccessories.co.uk

MLA PART CODE	EMPOWER2
DESCRIPTION	230V IP20 3W LED Emergency Downlight 6000K (maintained/non-maintained use)
NET WEIGHT (KG)	0.39
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 55 Length - 350 Height - 32 Recessed Depth - 30 Minimum Void - 80
CUT-OUT (MM)	Cut-out Diameter - 46
CONSTRUCTION	Construction - Die-cast aluminium Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	3
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	210
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	35.93
LUMENS EMERGENCY MODE (LM)	210
CIRCUIT WATTAGE (W)	5.8
CCT	6000K
LIGHT COLOUR	Daylight
RUNNING CURRENT (A)	0.051
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched

SELF-TEST	No
IC RATED	No
OPERATING TEMPERATURE	0~45°C
INPUT VOLTAGE	230V 50Hz
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598-2-22
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055559187622

Date Created: 24/07/2022 23:10

