# GLS BULB E27 1521LM 15W 2700K DIMMABLE 240 BEAM FROSTED INTEGRAL

ILGLSE27DC032



This 15W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a dimmable, warm light and brightness. With a 1521 lumen output, this lamp is one of only a few true 100W filament bulb replacements available today. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

#### **Details**

Quick Order Code: Barcode: Category: Range Name: Product Type: Market Segment: Warranty (Years):	114268 5055788212591 Lamps Everyday GLS Commercial indoor, Residential indoor 2
CE RoHS:	Yes
Physical Data	
Product Length (mm):	122
Product Width (mm):	60
Product Weight (g):	121
Material:	Aluminium, Polycarbonate
Base Term:	Edison screw
Bulb Base:	E27
Construction:	Aluminium and Plastic heat-sink, Injection moulded diffuser
Globe Finish:	Frosted
Globe Type:	GLS
Bulb Fixing:	Pendant, Wall, lamp stand, table lamp
Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting

15 15

#### **Electrical Data**

Power (W):	
Power Consumption (w):	

Power Factor:	0.9
Wattage equivalent (W):	100
Amperage (mA):	70
Dimming:	Dimmable
Driver IC Manufacturer:	Marvel
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes


# Light Data

Luminous Flux in Lumens (Im):	1521
Luminous efficacy (Im/W):	101
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	240, 200
Colour Rendering Index (CRI):	80
Compatible Dimmers:	Varilight JQP401W
Frequency Range (Hz):	50
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500

#### **Environment**

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40

## Portal.integral-led.com



## Packaging

Package Weight (g):	160
Package Length (mm):	135
Package Width (mm):	68
Package Depth (mm):	68
Qty per euro pallet:	1500

### Portal.integral-led.com