

**OMNI FILAMENT GLS BULB E27 1055LM 9.5W 2700K DIMMABLE 300 BEAM
CLEAR FULL GLASS INTEGRAL**

ILGLSE27DC124



Integral Filament Omni GLS Lamps utilise Filament LED technology to create a decorative look and wide beam angle that looks fantastic in ceiling pendants and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

Details

Quick Order Code:	263149
Barcode:	5055788260530
Category:	Lamps
Range Name:	Omni
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	104
Product Width (mm):	60
Product Weight (g):	33
Material:	Aluminium, Glass
Base Term:	Edison screw
Bulb Base:	E27
Construction:	Glass shell, Filament strip, Aluminium base
Globe Finish:	Clear
Globe Type:	GLS
Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting
Spot Type:	Filament

Electrical Data

Power Consumption (w):	9.5
Power Factor:	0.7
Wattage equivalent (W):	75
Amperage (mA):	55
Dimming:	Dimmable with compatible dimmers


Driver Included:	Yes
Electric Current:	AC
True Wattage Eq (W):	75
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	1055
Luminous efficacy (lm/W):	110
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	320
Colour Rendering Index (CRI):	80
Colour Type:	Single
Instant on (Less than 1 second):	Yes
LED Type:	Filament chip
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	E
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging

Package Weight (g):	110	Portal.integral-led.com
Package Length (mm):	70	

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Width (mm):	70
Package Depth (mm):	125