Product Code 05-E059-Z5-EH Installation Instructions 3D File Photometry Revit (BIM)



## SAM

Francesc Vilaró

Wall fixture IP66 SAM LED 3.5 SW 2700-3200-4000K ON-OFF Urban grey 269lm

#### Technical features

Luminaire total power: 3.5W Real lumens: 269 (3200K)

Real Im/W: 77

Correlated Colour Temperature (CCT): SW 2700-3200-4000K

Structure material: Aluminium Structure finish: Urban grey Diffuser material: Polycarbonate Diffuser finish: Semitransparent

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.50

THD%: 82.5

Useful life: 50,000h L80B20

Warranty: 5 años

Resistant to marine environments: Yes











#### Luminotechnic features

TM30 RG: 95 TM30 RF: 86

Melanopic ratio: 0.591


CRI: 80

MacAdam steps: 3

Photobiological risk: RG1

Lampholder	Quantity	Light source power (W)
LED	1	3.2W








Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 05-E059-Z5-EH Installation Instructions 3D File Photometry Revit (BIM)



# SAM

Francesc Vilaró

Wall fixture IP66 SAM LED 3.5 SW 2700-3200-4000K ON-OFF Urban grey 269lm

### Logistics

x 12

Net weight (kg): 0.3

Packaged weight (kg): 0.45

Packaging: 148mm x 54mm x 150mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.