## Knightsbridge

## DATASHEET



## SFR9000AT

Screwless 13A 2G DP switched socket - Anthracite

www.mlaccessories.co.uk

JET WEIGHT (KG)0.26VINISHAnthraciteNSERT COLOURBlackNSERT COLOURBlackDIMENSIONS (MM)Height - 87.5 Width - 147.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleCARTH TERMINALYesCOAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2ORIGIN OF MANUFACTUREChina	MLA PART CODE	SFR9000AT
INISHAnthraciteNSERT COLOURBlackNSERT COLOURBlackHeight - 87.5Width - 147.5DIMENSIONS (MM)Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleCOAD/MAX. LOAD13ATERMINALYesOAD/MAX. LOAD3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	DESCRIPTION	Screwless 13A 2G DP switched socket - Anthracite
NSERT COLOURBlackNSERT COLOURBlackDIMENSIONS (MM)Height - 87.5 Width - 147.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleCARTH TERMINALYes.OAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	NET WEIGHT (KG)	0.26
DIMENSIONS (MM)Height - 87.5 Width - 147.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleCARTH TERMINALYesCOAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2ORIGIN OF MANUFACTUREChina	FINISH	Anthracite
DIMENSIONS (MM)Width - 147.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleCARTH TERMINALYesCOAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2ORIGIN OF MANUFACTUREChina	INSERT COLOUR	Black
CONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYes.OAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2ORIGIN OF MANUFACTUREChina	DIMENSIONS (MM)	Width - 147.5
CLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH TYPEPouble PoleSARTH TERMINALYes.OAD/MAX. LOAD13A'ERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2ORIGIN OF MANUFACTUREChina	MINIMUM MOUNTING BOX DEPTH	25mm
P RATINGIP20NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYes.OAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	CONSTRUCTION	Construction - Premium grade steel
NPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleCARTH TERMINALYesCOAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	CLASS	I
WITCH TYPEDouble PoleCARTH TERMINALYesCOAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	IP RATING	IP20
EARTH TERMINALYesCOAD/MAX. LOAD13ACOAD/MAX. LOAD13ATERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	INPUT VOLTAGE	230V 50Hz
OAD/MAX. LOAD13A'ERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2ORIGIN OF MANUFACTUREChina	SWITCH TYPE	Double Pole
TERMINAL CAPACITY $3 \times 2.5 \text{mm}^2 \text{ or } 2 \times 4.0 \text{mm}^2$ VARRANTY $25 \text{year}(\text{s})$ MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	EARTH TERMINAL	Yes
VARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 1363-2DRIGIN OF MANUFACTUREChina	LOAD/MAX. LOAD	13A
MANUFACTURED IN ACCORDANCE WITH BS 1363-2   DRIGIN OF MANUFACTURE China	TERMINAL CAPACITY	3 x 2.5mm <sup>2</sup> or 2 x 4.0mm <sup>2</sup>
DRIGIN OF MANUFACTURE China	WARRANTY	25year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS 1363-2
ECLARATION OF CONFORMITY (HELD ON FILE)	ORIGIN OF MANUFACTURE	China
	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
AN 5056270819113	EAN	5056270819113

Date Created: 09/06/2023 11:53

ACCESSORIES LTD





