


ICON

GU10 Tilt Trimless Downlight - White on White



FX

GU10 SERIES



Easy Access Housing

Removable twist and lock system allowing for easy lamp access

Easy Installation

Loop in and out push in fast connector

Low Profile

Constructed using fire rated glass allowing for a low profile and improved lamp ventilation

Description

Our Icon GU10 offers a modern minimalist design that naturally blends into any environment. Pressed in steel and composed of fire rated glass allows this unit to have a very low profile, making it quick and easy to install, whilst offering improved ventilation to your LED bulb and in turn improving its lifespan.

Dimensions

Cut Out: Ø80mm

Diameter: Ø74mm

Height: 50mm

Plaster In frame: Ø106mm x 87mm

Light Source	LED GU10
Wattage	7W Max
Lamp included	No
Finish	RAL 9003
Class	Class 2
Product Reference	FD04PT-00

Optional Extras

The Insulation Guard allows this product to be covered by thermal and acoustic insulation e.g. loft insulation. Not suitable for blown insulation. Please ensure a max wattage of 7W when covering with insulation and utilising the insulation bracket.

Insulation Guard Reference: IC03



30, 60 and 90 Minutes Fire Rated



IP65 Rated, suitable for bathroom Zones 1, 2 & 3



Insulation Coverable when an Insulation Guard is installed



230V Mains Voltage powered



Mains Dimmable when a suitable lamp is installed



7 Year Domestic & 5 Year Commercial Extended Warranty