

## **OUH** INDUSTRIAL FAN HEATERS



**Function** Space heating in industrial buildings

**Application** Warehouses  
Factories  
Workshops

**Features** FIVE YEAR WARRANTY  
Robust all-steel construction  
Bracket for wall or ceiling mounting and hooks for vertical suspension  
Built-in adjustable thermostat plus overtemperature and heat purge devices  
Fitted with fused control circuit and contactor  
Optional switch provides on/off/fan only settings  
Remote-mounted programmable thermostats available  
Switch and/or thermostat can be connected to a chain of up to 16 heaters  
For multi-heater installations we recommend SystemX (page 54-55)

## OUH Industrial Fan Heaters

| Model   | kW  |
|---------|-----|
| OUH2-03 | 3.0 |
| OUH2-05 | 5.0 |
| OUH2-07 | 7.5 |
| OUH2-10 | 10  |
| OUH2-15 | 15  |
| OUH2-20 | 20  |
| OUH2-25 | 25  |

## Controls

|                                                                                     | Description                                                                   | Model   | Details  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|---------|----------|
|    | Switch (On/off/fan only)                                                      | OUH2-S  | Page 121 |
|   | Electronic programmable thermostat 16A                                        | RT16    | Page 112 |
|  | Wi-Fi electronic thermostat 16A (free app)                                    | WT16    | Page 113 |
|  | Optional remote air sensor for RT16 or WT16                                   | CXS     | Page 126 |
|  | Mechanical frost thermostat.<br>Overrides other thermostats and OUH2-S switch | RST3-IN | Page 110 |

## Technical

| kW  | Volts         | Airflow<br>(m³/h) | dB* @2m | Dimensions(mm) |     |     | Weight<br>(kg) |
|-----|---------------|-------------------|---------|----------------|-----|-----|----------------|
|     |               |                   |         | W              | D   | H   |                |
| 3.0 | 230 or 400/3N | 1100              | 60      | 435            | 405 | 320 | 18             |
| 5.0 | 230 or 400/3N | 1100              | 60      | 435            | 405 | 320 | 18             |
| 7.5 | 230 or 400/3N | 1100              | 60      | 435            | 405 | 320 | 18             |
| 10  | 400/3N        | 1100              | 60      | 435            | 405 | 320 | 18             |
| 15  | 400/3N        | 3150              | 62      | 565            | 485 | 445 | 37             |
| 20  | 400/3N        | 3150              | 62      | 565            | 485 | 445 | 37             |
| 25  | 400/3N        | 3150              | 62      | 565            | 485 | 445 | 37             |

\*Noise levels are factory tested not laboratory tested

Where roof height exceeds 4m we recommend using our DSU destratification units (see pages 58-59).

**Case studies pages 56 & 57**



### Maranello Ferrari

**Location:** Egham, Surrey

**Installed:** 2 x 20kW Industrial Fan Heaters



**Quaife Engineering Ltd**

**Location:** Sevenoaks, Kent

**Installed:** 2 x 25kW Industrial Fan Heaters

3 x 10kW Industrial Fan Heaters