
Illuma

Technical Data Sheet

Range Name:	Lumapar
Product Type:	Spotlights
Product Code:	T340506-BL/SDL/830
Body Colour:	Black
Mounting:	Track Mounted
Track Adaptor:	SDL - 1-Circuit Switched Track Adaptor
Pendant Stem Length(mm):	-
Vertical Mount:	-
Environment:	Interior
Size(mm)	120 x 87 x 60
Cut Out(mm):	-
Recessed Depth(mm):	-
Vertical Tilt(°):	90°
Horizontal Rotation(°):	355°
Light Source:	LED
Lamp Type:	CREE LED
Lamp Included:	In Built
Lamp Base:	-
Lamp Life(Hours):	50000 hours
Lumen Output(Im):	500lm
Colour Temperature(k):	3000k Warm White
CRI(Ra):	82
Beam Angle(°):	6°
Lense:	-
Voltage(V):	230VAC
Total System Power(W):	7.7W
Lamp Current(A):	0.035
Power Factor:	0.95
Luminaire Efficacy(Im/W):	51 lm/W
Class:	Class 1
Gear:	Built In
EAN Code:	-
Dimmability:	Leading/Trailing Edge Dimmable
Emergency:	-
IP Rating:	IP20
Weight(kg):	0.3kg
Housing Material:	Aluminium
Material Finish:	Powder Coated
Guarantee:	5 Year Guarantee





Images, line drawings and measurements illustrated may, in some cases be approximate and for guidance only. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. Illuma Lighting are continually developing and improving its products. Technical specifications subject to change without prior notice. For full terms and conditions visit: <u>https://www.illuma.co.uk/terms.htm</u>

Illuma Lighting (*Trading as a divison of Searchlight Electric Ltd.*) Sills Road, Willow Farm Business Park Castle Donington Derbyshire, DE74 2US United Kingdom © Illuma 2021

T +44(0) 1332 818 200 F +44(0) 1332 818 222 E sales@illuma.co.uk W www.illuma.co.uk

VAT Registration No. 149697311 Registered in England No: 1169504 Certification BS EN ISO 9001:2008