Xnightsbridge


DATASHEET



SPKEVF

SpektroLED Evo Fixed - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT

www.mlaccessories.co.uk



MLA PART CODE	SPKEVF
DESCRIPTION	SpektroLED Evo Fixed - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT
NET WEIGHT (KG)	0.23
DIFFUSER	Prismatic
DIMENSIONS (MM)	Diameter - 90 Recessed Depth - 43 Minimum Void - 45
CUT-OUT (MM)	Cut-out Diameter - 70
CONSTRUCTION	Construction - Pressed steel
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	5 / 7
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	580/600/630/620/780/810/870/840
LUMENS LIGHT SOURCE ONLY (LM)	1020
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	144
CIRCUIT WATTAGE (W)	7.1
сст	2700/3000/4000/6000K
LIGHT COLOUR	ССТ
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.037
DISPLACEMENT FACTOR	>0.7
SVM	0.008
PST-LM	0.297
BEAM ANGLE (DEGREES)	60
LIFE SPAN (HRS)	50,000
L70B10 LIFESPAN (HRS)	50,000





Xnightsbridge

DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
WEB-JOIST RATED	30 minutes
IC RATED	Yes
ACOUSTIC RATED	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270840865

Date Created: 26/04/2024 15:34





