

Illuma

Technical Data Sheet

Range Name:Gridspot LEDProduct Type:SpotlightsProduct Code:T324038-WH/SDL/830Body Colour:WhiteMounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Pendant Stem Length(mm):-Size(mm)InteriorSize(mm)175 × 90 × 160Cut Out(mm):-Pertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):38°Beam Angle(°):38°Light System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/W
Product Code:T324038-WH/SDL/830Body Colour:WhiteMounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)175 × 90 × 160Cut Out(mm):-Perdeared Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life(Hours):3000k hoursColour Temperature(k):3000k Warm WhiteCRI(Ra):38°Beam Angle(°):38°Voltage(V):45.1WLamp Current(A):0.197Power Factor:0.98
Body Colour:WhiteMounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)175 x 90 x 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life(Hours):50000 hoursLumen Output(Im):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WPower Factor:0.98
NoteTrack MountedMounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)175 × 90 × 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Colour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WPower Factor:0.98
Track Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)175 × 90 × 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):38°Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WPower Factor:0.98
Pendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)175 x 90 x 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Urtical Tilt(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Colour Temperature(k):3000 hoursCut Rit(Ra):S000 hoursBeam Angle(°):38°Voltage(V):240VTotal System Power(W):4.197Power Factor:0.98
Vertical Mount:-Environment:InteriorSize(mm)175 x 90 x 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):38°Ream Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Environment:InteriorSize(mm)175 × 90 × 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lumen Output(Im):4000lmColour Temperature(k):300k Warm WhiteCRI(Ra):85Beam Angle(°):240VTotal System Power(W):0.197Power Factor:0.98
Size(mm)175 x 90 x 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lumen Output(Im):4000lmColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WPower Factor:0.98
Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lumen Output(Im):50000 hoursLumen Output(Im):3000k Warm WhiteCRI(Ra):3000k Warm WhiteBeam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.98
Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WPower Factor:0.98
Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):5000 hoursLumen Output(Im):4000ImCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):0.197Power Factor:0.98
Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Lamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Lamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Lamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):240VTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Lumen Output(Im): 4000lm Colour Temperature(k): 3000k Warm White CRI(Ra): 85 Beam Angle(°): 38° Voltage(V): 240V Total System Power(W): 45.1W Lamp Current(A): 0.197 Power Factor: 0.98
Colour Temperature(k): 3000k Warm White CRI(Ra): 85 Beam Angle(°): 38° Voltage(V): 240V Total System Power(W): 45.1W Lamp Current(A): 0.197 Power Factor: 0.98
CRI(Ra): 85 Beam Angle(°): 38° Voltage(V): 240V Total System Power(W): 45.1W Lamp Current(A): 0.197 Power Factor: 0.98
Beam Angle(°): 38° Voltage(V): 240V Total System Power(W): 45.1W Lamp Current(A): 0.197 Power Factor: 0.98
Voltage(V): 240V Total System Power(W): 45.1W Lamp Current(A): 0.197 Power Factor: 0.98
Total System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98
Lamp Current(A): 0.197 Power Factor: 0.98
Power Factor: 0.98
Luminaire Efficacy(Im/W): 89 Im/W
Class: Class 1
Gear: Built In
EAN Code: 5030785129295
Dimmability: -
Emergency: -
IP Rating: IP20
Weight(kg): 1.15kg
Housing Material: Aluminium
Material Finish: Powder Coated
Guarantee: 5 Year Guarantee







Images, line drawings and measurements illustrated may, in some cases be approximate and for guidance only. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. Illuma Lighting are continually developing and improving its products. Technical specifications subject to change without prior notice. For full terms and conditions visit: <u>http://www.illuma.co.uk/terms.htm</u>

Illuma Lighting (*Trading as a divison of Searchlight Electric Ltd.*) Sills Road, Willow Farm Business Park Castle Donington Derbyshire, DE74 2US United Kingdom © Illuma 2016

T +44(0) 1332 818 200 F +44(0) 1332 818 222 E sales@illuma.co.uk W www.illuma.co.uk

VAT Registration No. 149697311 Registered in England No: 1169504 Certification BS EN ISO 9001:2008