Fire Rated Downlight 6W (40W) 4000K 440Im 38 deg beam angle 70mm-75mm cut-out Dimmable

Quick Order Code: 391910 / Page: 1



As LED products produced using new technologies are used with old dimmer technology, achieving effective and smooth dimming can be challenging. For this dimmable downlight we have tested, and recommend, the dimmer detailed in the specification below.

Product Details

Partcode: ILDLFR70B003 Check Code: 391910 Range Name: Low-profile Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: Fire Rated Warranty: 3 Years CE / RoHS: Yes

Physical Data

Product Finish: Matt white Spot Type: COB Optic: Clear Refractor Material: Aluminium alloy, Iron, Intumescent material, Steel Construction: Extruded Aluminium heat-sink, Iron body, Steel springs and mounting plate

integral LED

Quick Order Code: 391910 / Page: 2

Physical Data

Length: 58mm Diameter: 85mm Weight (Unpackaged Single Unit): 280g Luminaire Fixing: Recess mounted Fire Rating: 30, 60, 90

Electrical Data

Voltage Range: 220-240V Power Consumption: 6.0 Watts Driver included: Yes Electric Current: AC Ampage: 300.00mA Frequency Range: 50/60 Hz Power Factor: >=0.90 Wattage Equivalent: 40 Watts Dimming: Dimmable with compatible dimmers Compatible Dimmer(s): Varilight JQP401W LVD Certified: Yes EN: EN-60598

Light Data


Lumens: 440lm Lumens per Watt: 73.0lm/W Beam Angle: 38° Correlated Colour Temperature (CCT): 4,000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=80 LED Type: Chip on board (COB) Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

www.integral-led.com



Quick Order Code: 391910 / Page: 3

Environmental



Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 45 degrees IP (Ingress Protection) Rating: IP65 Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788223405 Packaged Weight (Unit of 1): 350g Length (unit of 1): 105mm Width (unit of 1): 100mm Depth (unit of 1): 80mm

Outer packaging info available on website

Product data last updated on: Wednesday, November 9, 2016 - 11:47

www.integral-led.com