

Illuma

Product Type:SpatlightsProduct Code:T334038-WH/SDL/830Pendart Stem Length (m)Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length (m):-Vertical Mount:InteriorSize(mn)205 x 90 x 160Cut Out(mn):-Recessed Depth (m):-Vertical Rotation (°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life (Hours):50000 hoursLumen Output (lm):4000lmColour Temperature (k):300xk Warm WhiteCRI(Ra):85Beam Angle (°):38°Voltage (V):0.197Power Factor:0.98Luminaire Efficacy (lm/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Imaging Material:AluminiumFindelici:320 AdditionImaging Material:AluminiumMaterial Finish:Power CoatedGuarantee:5 Year Guarantee	Range Name:	Gridspot LED Anti Glare
Body Colour:WhiteMounting:Track MountedMounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)205 × 90 × 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Included:In BuiltLamp Base:-Colour Temperature(k):30000 hoursLumen Output(Im):4000ImColour Temperature(k):300VACVoltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Pating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Product Type:	Spotlights
Mounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:InteriorSize(mm)205 × 90 × 160Cut Out(mm):-Recessed Depth(mm):90°Vertical Tilt(°):90°Vertical Tilt(°):SDS°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLumen Output(Im):3000 hoursLumen Output(Im):3000k Warm WhiteColour Temperature(k):3000k Warm WhiteCRI(Ra):S3Beam Angle(°):38°Voltage(V):0.197Power Factor:0.98Luminaire Efficacy(Im/W):S9 Im/WClass:Class 1Gear:Built InEAN Code:-Imagintity:-Power Factor:122kgHensing:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Product Code:	T334038-WH/SDL/830
Mounting:Track MountedTrack Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:InteriorSize(mm)205 × 90 × 160Cut Out(mm):-Recessed Depth(mm):90°Vertical Tilt(°):90°Vertical Tilt(°):SDS°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLumen Output(Im):3000 hoursLumen Output(Im):3000k Warm WhiteColour Temperature(k):3000k Warm WhiteCRI(Ra):S3Beam Angle(°):38°Voltage(V):0.197Power Factor:0.98Luminaire Efficacy(Im/W):S9 Im/WClass:Class 1Gear:Built InEAN Code:-Imagintity:-Power Factor:122kgHensing:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated		
Track Adaptor:SDL - 1-Circuit Switched Track AdaptorPendant Stem Length(mm):-Vertical Mount:NetrorEnvironment:InteriorSize(mm)205 × 90 × 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLumen Output(Im):4000lmColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):203VACTotal System Power(W):45.1WLuminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Image:1Power Factor:1.22kgHenting:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Body Colour:	White
Pendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)205 x 90 x 160Cut Out(mm):-Recessed Depth(mm):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Type:50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Pating:1.22kgHengency:1.22kgHousing Material:AluminiumMuterial Finish:9 power Coated	Mounting:	Track Mounted
Vertical Mount:-Environment:InteriorSize(mm)205 x 90 x 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lumen Output(Im):4000InColour Temperature(k):3000k Warm WhiteCRI(Ra):230VACTotal System Power(W):45.1WLuminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Faring::Pweifficacy(Im/W):122/2Pimability:-Faring:122/2Furing:122/2Furing:122/2Furing:122/2Furing:122/2Furing:9 Powder Coated	Track Adaptor:	SDL - 1-Circuit Switched Track Adaptor
Environment:InteriorEnvironment:InteriorSize(mm)205 × 90 × 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):300VACTotal System Power(W):45.1WLumiarie Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-FAN Code:-Power Fattor:1.22kgHousing Material:AluminiumMaterial Finish:Power Coated	Pendant Stem Length(mm):	-
Size(mm)205 x 90 x 160Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Colour Temperature(k):3000 hoursCuttage(Y):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Class:Class 1Gear:Built InEAN Code:-Dimmability:-FAN Code:-Pating:N20Weight(kg):1.22kgHousing Material:AluminumMaterial Finish:Powder Coated	Vertical Mount:	-
Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Jase:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteBeam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Pinzel2.22kgIp Rating:1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Environment:	Interior
Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteRRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLuminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Imability:-Imability:1.22kgWeight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Power Coated	Size(mm)	205 x 90 x 160
Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):33°Yoltage(V):230VACTotal System Power(W):45.1WLuminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Frergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:Power Coated	Cut Out(mm):	-
Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLuminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-FM Code:-Powerfactor:0.2Jumation (kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Recessed Depth(mm):	-
Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLuminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Farting:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Power Coated	Vertical Tilt(°):	90°
Lamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000lmColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-FP20IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Power Coated	Horizontal Rotation(°):	355°
Lamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Power Coated	Light Source:	LED
Lamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Factor:0.22 kgIve Specificacy(Im/W):1.22 kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lamp Type:	CREE LED
Lamp Life(Hours):50000 hoursLumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WGear:Built InEAN Code:-Dimmability:-Factor:0.197Weight(kg):1.22kgHousing Material:AluminiumPower Coated-	Lamp Included:	In Built
Lumen Output(Im):4000ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Factor:0.197Weight(kg):1.22kgHousing Material:AluminiumPower Coated-	Lamp Base:	-
Colour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Farergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lamp Life(Hours):	50000 hours
CRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WGear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lumen Output(Im):	4000lm
Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Colour Temperature(k):	3000k Warm White
Voltage(V):230VACTotal System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Factor:1.22kgWeight(kg):AluminiumMaterial Finish:Powder Coated	CRI(Ra):	85
Total System Power(W):45.1WLamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):AluminiumMaterial Finish:Powder Coated	Beam Angle(°):	38°
Lamp Current(A):0.197Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):AluminiumMaterial Finish:Powder Coated	Voltage(V):	230VAC
Power Factor:0.98Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Total System Power(W):	45.1W
Luminaire Efficacy(Im/W):89 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lamp Current(A):	0.197
Class 1Gear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Power Factor:	0.98
Gear:Built InEAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Luminaire Efficacy(Im/W):	89 lm/W
EAN Code:-Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Class:	Class 1
Dimmability:-Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Gear:	Built In
Emergency:-IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	EAN Code:	-
IP Rating:IP20Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Dimmability:	-
Weight(kg):1.22kgHousing Material:AluminiumMaterial Finish:Powder Coated	Emergency:	-
Housing Material:AluminiumMaterial Finish:Powder Coated		IP20
Material Finish: Powder Coated		1.22kg
		Aluminium
Guarantee: 5 Year Guarantee	Material Finish:	Powder Coated
	Guarantee:	5 Year Guarantee

Technical Data Sheet







Images, line drawings and measurements illustrated may, in some cases be approximate and for guidance only. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. Illuma Lighting are continually developing and improving its products. Technical specifications subject to change without prior notice. For full terms and conditions visit: <u>http://www.illuma.co.uk/terms.htm</u>

Illuma Lighting (*Trading as a divison of Searchlight Electric Ltd.*) Sills Road, Willow Farm Business Park Castle Donington Derbyshire, DE74 2US United Kingdom © Illuma 2017

T +44(0) 1332 818 200 F +44(0) 1332 818 222 E sales@illuma.co.uk W www.illuma.co.uk

VAT Registration No. 149697311 Registered in England No: 1169504 Certification BS EN ISO 9001:2008