APRILIA SQUARE ADJUSTABLE **5762** sku 1256027



PRODUCT SPECIFICATION

GENERAL


FINISH: Anodised Aluminium CABLE LENGTH: 450 (mm) MAIN MATERIAL: Metal - Aluminium GROSS WEIGHT: 0.31 (Kg) H: 95mm W: 95mm D:68.5mm DIMENSIONS: CE (Class III) CLASS: INSTALLATION ORIENTATION: Ceiling Mount **IP RATING:** IP20 86mm/3-3/8" CUT OUT HOLE: BATHROOM ZONE: Zone 3 **RECESS DEPTH:** 150 (mm) VOLTAGE: Constant Current 350 (mA) FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials LAMP LIGHT SOURCE: COB LED MACADAM ELLIPSE: 3-Step MAXIMUM WATTAGE: 6.1W UGR: To Be Advised MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** 36.1 (Degrees) LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: 35 (Degrees) LUMINOUS FLUX: 604.8 (lm) ROTATION ADJUSTMENT ANGLE: 360 (Degrees) COLOUR TEMP: 2700 (K) AVERAGE LIFESPAN: 36,300 (Hrs) CRI: 80 L70: To Be Advised R9: 8.0 **ELECTRICAL** SWITCHED: No SUPPLY FREQUENCY: Not Applicable DIMMABLE: Yes DRIVER / BALLAST VOLTAGE: Not Applicable DIMMING METHOD: Control Gear Dependant DRIVER AVERAGE LIFESPAN: Not Applicable DRIVER OUTPUT CURRENT: Not Applicable EFFICACY: 97.55(lm/W) DRIVER OUTPUT VOLTAGE: DRIVER/BALLAST INCLUDED? Not Applicable No


ADDITIONAL INFORMATION





BOX QUANTITY x 20

CE









T: +44 (0) 1279 427001

sales@astrolighting.com

www.astrolighting.com