

BORG TRIMLESS 65 2700K 7534

SKU 1212028

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Matt White	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Mild Steel	GROSS WEIGHT:	0.39 (Kg)
DIMENSIONS:	H: 65mm W: 65mm D: 42mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Wall Mount - Vertical	IP RATING:	IP20
CUT OUT HOLE:	L: 115mm W: 67mm	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	42 (mm)	VOLTAGE:	Constant Current 700 (mA)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Not Applicable

LAMP

LIGHT SOURCE:	High Power LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	2W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Not Applicable
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	70	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	60,000 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	6.9		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER / BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	17.07 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Not Applicable

ADDITIONAL INFORMATION



Product tested with 1836 - LED Driver CC 250/350/500/700mA DALI Dim



BOX QUANTITY x 16

PRODUCT ELEVATIONS

