

TKE/P 32



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.

Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66, IP68 (5 bar 30 min)
Product Color	RAL 7035
Thread type	M
Ø Connection thread D	32
Lead	1,5
Length screw-in thread L	12 mm
Key width SW	36 mm
Total length TL	42 mm - 51 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques fitting	15 N/m
Install. torques cap nut	4 N/m
Impact category	4
Order no. RAL 7035	10106242
Type	TKE/P 32
Packing unit	1
ETIM-Classification	EC000441

Description:

IP 68 Plastic cable gland. ESKV 32/ MFD 1 x 16 mm Tails and 2 x 9 mm Earth. Kit contains insert, locknut and blanking insert.

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

20.11.2018

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk