PH Pew Heaters

new



PH65

PH45





PH30

PH Series - ideal for unobtrusive installation under a church pew

- **An economic means of heating a church congregation**
- **Minimal pre-heating required ensuring low running costs**
- **Visually unobtrusive**

Features

- Robust all-steel construction
- Dark brown paint finish
- Fixed directly to a pew's backboard or mounted on floor or suspension brackets
- 20mm cable knockouts at both ends for electrical connection
- External guard not required



PH Pew heater installed under a church pew

Heater Range

Model	Length (mm)	kW
PH30	525	0.3
PH45	702	0.45
PH65	948	0.65



PHF optional floor brackets

Heater Technical Data

Model	kW	Volts	Dimensions (mm)			Weight (kg)
			L	D	H	
PH30	0.3	230	525	58	168	2.5
PH45	0.45	230	702	58	168	3.2
PH65	0.65	230	948	58	168	4.2




PHB optional suspension brackets

Optional Brackets (for pews without backboards)

Type	Description	Model
Bracket	Floor (pair) assembled height 204mm	**PHF**
Bracket	Suspension (pair) assembled height 325mm	**PHB**

Pew Heater Section Table

Space Between Seat Supports (mm)		Recommended Heater
Minimum	Maximum	
600	750	PH30
750	1000	PH45
1000	1500	PH65
1500+		Multiple Heaters



Spaces between seat supports



Pew heaters fitted directly to pew backboards





Pew heater installed using floor brackets – suspension brackets are also available