



Safe-D U-Clip 40 For 38mm+ Trunkings














Safe-D U-Clip 40 is ideal for fitment in 38mm or 40mm non-metallic trunking bases, or to provide a first-fix solution for securing cables direct to surfaces.

Installers should use a fire-rated fixing, such as D-Line D-Fixings, and then simply fold-over tabs to secure cables.

1st fix clips, then 2nd fix cables!



- Certified for 2 hours at 970°C
- Fully safety tested and certified to BS5839 part 1 compliant
- Thumb friendly, easy fold side-tabs
- · Non-corrosive coating
- Ideal for ceiling voids, or popular PVC trunking
- Rounded edges for easy handling





Safe-D 40 Fire Rated Clips For 38mm+ Trunkings

Product Specification

Produced from high temperature steel	 Can withstand temperatures of up to 970°C for 2 hours Safe-D Clips maintain strength after bending of side-tabs
U-shaped design	 Easy to handle Side-tabs fold-over to secure cables
Fold over rounded tabs	 20mm wide side-tabs & pliable gauge combine for quick and easy folding Smooth & rounded edges, as required by design code BS7671 s522.8.11, to protect soft-skin cables etc (and user friendly!)
Pre-drilled hole in base (6mm diameter)	Accepts shot-fire or screw-fixed steel fixings (Select suitable fixing type according to substrate)
Passivated finish	Protects against corrosive elements
Fully tested & certified	 Complies with requirements of BS5839 part 1 (2002 section 26.2d); BSEN50200:2000; & BS8434-1:2003
Weight	• 7.6g Each