## **Product datasheet** Characteristics

# **GU1242TSS**

Ultimate Flat plate - 2-way switch - 4 gangs stainless steel



lai

TTT CALL		
Range of product	Ultimate	-
Range	Ultimate	
Aesthetic name	Flat plate	
Product or component type	Switch	
Control type	Toggle switch	,
Switch function	2-way	-
Rated current	16 AX at 230 V AC	

### Complementary

Main		
Range of product	Ultimate	
Range	Ultimate	
Aesthetic name	Flat plate	
Product or component type	Switch	·
Control type	Toggle switch	
Switch function	2-way	
Rated current	16 AX at 230 V AC	
Commissions		
Connections - terminals	Screw terminals	
Material	Steel	
Quantity per set	Set of 1	
Number of gangs	4 gangs	:
Device mounting	Wall mounted	
Height	88 mm	
Width	148 mm	
Depth	36 mm	
Environment		:
Standards	BS EN 60669-1	
IP degree of protection	IP20	
Offer Sustainability		:
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		
Warranty	18 months	
Con 5, 2040		

#### Environment

Standards	BS EN 60669-1	 2
IP degree of protection	IP20	

#### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	<u>.</u> 2 2.
Circularity Profile	No need of specific recycling operations	

#### Contractual warranty

Warranty	18 months