



ATORLED5/110V/M3

Tornado 110V LED - Self-Test Emergency 28W



Features

LED Performance allows point-to-point replacement of existing fluorescent luminaires

Suitable for all types of 110V site lighting

Light output exceeds performance of T8 and T5 fluorescent

Unique luminaire fixing clip design allows option of mounting onto BESA box

Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

LED lifespan L70 30,000 hours

Non-dimmable

Self-test emergency as standard

General Information

Lamp Type	LED
Colour / Finish	Yellow
Emergency	Yes
Self Test	Yes
IP Rating	IP65
IK Rating	IK07
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface/Suspended
LED Life	L70 35,000hrs
Warranty (Years)	3
CE Mark	Yes
Length (mm)	1566
Width (mm)	85
Height (mm)	75

Technical Information

Wattage	28W
Lumens Delivered	3230lm
Lm/W	115lm
CRI	Ra 80
CCT	4000K
Input	100/240V
Hertz	50Hz
Operating Temp	-10 to 40°C

	Code	A	B	C	D
	ATORLED2/110V	656	360	75	85
	ATORLED4/110V	1266	860	75	85
	ATORLED5/110V	1566	960	75	85
	ATORLED2X2/110V	656	360	75	118
	ATORLED2X4/110V	1266	860	75	118
	ATORLED2X5/110V	1566	960	75	118

Datasheet generated from <https://www.electrika.com> last updated Wednesday, August 28, 2019 1:04:37 PM