Product datasheet Characteristics

GU3220WSS

Ultimate Flat plate - switched socket - 2 gangs - stainless steel



Main

Man		
Range	Ultimate	
Device application	Power supply	
Aesthetic name	Flat plate	
Product or component type	Switched socket	
Rated current	13 A at 230 V AC 50 Hz	
Fixing mode	By screws M3.5 x	
Colour tint	Stainless steel	

Complementary

Device presentation	Complete product	
Outlet poles configuration	1P	
Outlet standard description	3 pins	
Outlet standard	British	
Actuator	Rocker	
Number of gangs	2 gangs	
Earth circuit	Standard earth	
Pilot light	Without neon indicator	-
Device mounting	Wall mounted	
Connections - terminals	Screw terminal	
Material	Stainless steel	j
Quantity per set	Set of 1	
Height	88 mm	
Width	148 mm	
Depth	30 mm	
Socket number	2	
Mounting mode	Horizontal	

Environment

IP degree of protection	IP20
Standards	BS

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Warranty	18 months