# Product datasheet Characteristics

# **GU3251WSS**

Ultimate Flat plate - unswitched floor socket - 1 gang - stainless steel



Aesthetic name	Flat plate
Product or component type	Socket-outlet
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x
Colour tint	Stainless steel

#### Complementary

Complementary		
Device presentation	Complete product	<del>-</del>
Outlet poles configuration	1P	<u>.</u>
Outlet standard description	3 pins	
Outlet standard	British	
Number of gangs	1 gang	# 10 m
Earth circuit	Standard earth	.i.
Pilot light	Without neon indicator	<u> </u>
Device mounting	Wall mounted	
Connections - terminals	Screw terminal	9
Material	Steel	
Quantity per set	Set of 1	+
Height	88 mm	
Width	88 mm	
Depth	27 mm	d p
Socket number	2	<u> </u>

### Environment

IP degree of protection	IP20	
Standards	BS 1363	—

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	ner: This c
Mercury free	Yes	sclain———

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Contractual warranty	
Warranty	18 months