Product datasheet Characteristics

GU5413WSS

Ultimate Screwless flat plate - switched fused connection - steel



William	
Aesthetic name	Screwless flat plate
Product or component type	Switched fused connection
Switch function	Switch
Colour tint	Steel White

Complementary

Pilot light	without neon indicator
Number of gangs	1 gang
Material	Steel
Mounting support	Wall mounted
Fixing mode	By screws
Rated current	13 A at 230 V AC
Connections - terminals	Screw terminals
Quantity per set	Set of 1
Height	88 mm
Width	88 mm
Depth	26 mm

Environment

IP degree of protection	IP20	— şti.
Standards	BS 1363	

Offer Sustainability

Aesthetic name	Screwless flat plate	
Product or component type	Switched fused connection	
Switch function	Switch	
Colour tint	Steel White	
Complementary		
Pilot light	without neon indicator	
Number of gangs	1 gang	
Material	Steel	
Mounting support	Wall mounted	
Fixing mode	By screws	
Rated current	13 A at 230 V AC	
Connections - terminals	Screw terminals	
Quantity per set	Set of 1	
Height	88 mm	
Width	88 mm	
Depth	26 mm	
Environment		
IP degree of protection	IP20	
Standards	BS 1363	
Offer Sustainability		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		

Contractual warranty

Warrantv	18 months
vvarianty	10 1110111113