Product datasheet Characteristics

GU6412CSS

Ultimate Screwless dimmer switch 400W/VA, 1gang, 2way, main & LV, st.steel



Main

Range of product	Ultimate	
Range	Ultimate	
Aesthetic name	Screwless flat plate	
Product or component type	Dimmer	
Device application	Control	
Load type	Incandescent lamp 230 V AC halogen lamp: 400 W	
Colour tint	Stainless steel	
Quantity per set	Set of 1	
Complementary		
Switch function	2-way	
Device mounting	Wall mounted	
Dimmer application	Resistive load Inductive load	
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	1 gang	
Connections - terminals	Screwless terminals	
Height	88 mm	
Width	88 mm	
Depth	25 mm	
Environment		
Standards	BS EN 60669-2-1	
IP degree of protection	IP20	
Offer Sustainability		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	

Complementary

Switch function	2-way	
Device mounting	Wall mounted	
Dimmer application	Resistive load Inductive load	
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	1 gang	
Connections - terminals	Screwless terminals	
Height	88 mm	
Width	88 mm	
Depth	25 mm	

Environment

Standards	BS EN 60669-2-1	, de
IP degree of protection	IP20	a

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months