# Product datasheet Characteristics

## **GU6442CSS**

Ultimate Screwless dimmer switch 250W/VA, 4gang, 2way, main & LV, st.steel



		ذ.
Range of product	Ultimate	# # # # # # # # # # # # # #
Range	Ultimate	
Aesthetic name	Screwless flat plate	
Product or component type	Dimmer	
Device application	Control	
Load type	Incandescent lamp 230 V AC halogen lamp: 250 W	to to to
Colour tint	Stainless steel	
Quantity per set	Set of 1	

#### Complementary

Device mounting Wall mounted  Dimmer application Inductive load Resistive load  [Ue] rated operational voltage 230 V AC 50 Hz  Number of gangs 4 gangs  Connections - terminals Screwless terminals Height 88 mm  Width 148 mm	· · · · · · · · · · · · · · · · · ·		<u>:</u>
Dimmer application Inductive load Resistive load [Ue] rated operational voltage 230 V AC 50 Hz  Number of gangs 4 gangs  Connections - terminals Screwless terminals  Height 88 mm  Width 148 mm	Switch function	2-way	
Resistive load  [Ue] rated operational voltage 230 V AC 50 Hz  Number of gangs 4 gangs  Connections - terminals Screwless terminals  Height 88 mm  Width 148 mm	Device mounting	Wall mounted	
Number of gangs 4 gangs  Connections - terminals Screwless terminals  Height 88 mm  Width 148 mm	Dimmer application		
Connections - terminals Screwless terminals Height 88 mm Width 148 mm	[Ue] rated operational voltage	230 V AC 50 Hz	
Height 88 mm Width 148 mm	Number of gangs	4 gangs	
Width 148 mm	Connections - terminals	Screwless terminals	
	Height	88 mm	
Depth 35 mm	Width	148 mm	
	Depth	35 mm	

### Environment

Standards	BS EN 60669-2-1	
IP degree of protection	IP20	q

#### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	F
RoHS exemption information	Yes	

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months