Product datasheet Characteristics

GU5011

Ultimate Slimline - switched fused connection neon - white





Main

Range	Ultimate
Device application	Protection
Aesthetic name	Slimline
Product or component type	Switched fused connection
Switch function	Switch
Colour tint	White

Complementary

Main		
Range	Ultimate	
Device application	Protection	
Aesthetic name	Slimline	
Product or component type	Switched fused connection	
Switch function	Switch	
Colour tint	White	
Complementary		
Complementary Pilot light	Red neon indicator	
Number of gangs	1 gang	
Material	Urea (carbamide)	
Mounting support	Wall mounted	
Fixing mode	By screws 13 A at 230 V AC	
Rated current		
Connections - terminals	Screw terminals	
Quantity per set	Set of 10	
Height	86 mm	
Width	86 mm	
Depth	26 mm	
Fuse type	Blade type	
Environment		
IP degree of protection	IP20	
Standards	BS 1363	
Offer Sustainability		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Can 0, 2040		

Environment

LITTION		
IP degree of protection	IP20	
Standards	BS 1363	

Offer Sustainability

oduct out of EU RoHS legal scope)
(

EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

|--|