Product datasheet Characteristics

GU3050

Ultimate Slimline - unswitched socket - 1 gang - white



lai

		2.
Aesthetic name	Slimline	
Product or component type	Unswitched socket	
Rated current	13 A at 230 V AC 50 Hz	
Fixing mode	By screws M3.5 x	
Colour tint	White moulded matt	

Complementary

Complementary		
Device presentation	Complete product	**************************************
Outlet poles configuration	1P	
Outlet standard description	3 pins	
Outlet standard	British	\ !!
Number of gangs	1 gang	
Earth circuit	Standard earth	
Pilot light	Without neon indicator	
Device mounting	Wall mounted	ţ
Connections - terminals	Screw terminal	
Material	Urea (carbamide)	
Quantity per set	Set of 10	*
Height	86 mm	
Width	86 mm	
Depth	26 mm	
Socket number	2	

Environment

IP degree of protection	IP20	—. <u>=</u>
Standards	BS 1363	—. <u>s</u>

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	ner: This c
Mercury free	Yes	sclain———

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Contractual warranty	
Warranty	18 months