## **Product datasheet** Characteristics

# GU3060

Ultimate Slimline - unswitched socket - 2 gangs white



#### Main

Man	
Aesthetic name	Slimline
Product or component type	Unswitched socket
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x
Colour tint	White moulded matt

### Complementary

Main		
Aesthetic name	Slimline	:
Product or component type	Unswitched socket	
Rated current	13 A at 230 V AC 50 Hz	
Fixing mode	By screws M3.5 x	
Colour tint	White moulded matt	
Complementary		
Device presentation	Complete product	;
Outlet poles configuration	1P	
Outlet standard description	3 pins	
Outlet standard	British	
Number of gangs	2 gangs	:
Earth circuit	Standard earth	
Pilot light	Without neon indicator	
Device mounting	Wall mounted	
Connections - terminals	Screw terminal	
Material	Urea (carbamide)	
Quantity per set	Set of 5	
Height	86 mm	:
Width	146 mm	
Depth	26 mm	
Environment		
IP degree of protection	IP20	
Standards	BS 1363	
Offer Sustainability		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	l
RoHS exemption information	Yes	
Com 0, 2040		

#### **Environment**

ZIIVII OI III II OI II			
IP degree of protection	IP20		
Standards	BS 1363		

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	-
RoHS exemption information	Yes	

China RoHS Regulation  China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information		
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		
Warranty	18 months	