

DIGITAL THERMOSTATS



KingShields range of thermostats are ideal for controlling heating and air conditioning systems.

- Displays both room and set temperature
- Internal switch selector for heat or air conditioning operating
- 2 wire operation



TH1-C



THP1-C



THPW1-CA
THPW1-CB
THPW1-CC
THPW1-CD
THPW1-CE

	TH1-C	THP1-C	THPW1-CA THPW1-CB THPW1-CC THPW1-CD THPW1-CE
Product Finish	White	White	White
Description	Digital Thermostat - Displays both room & set temperature	Programmable Digital Thermostat	Wireless Programmable Digital Thermostat (wireless version of the THP1-C)
Product Dimensions	H73 x W113 x D30mm	H83 x W131 x D31mm	H83 x W131 x D31mm
Product weight without batteries	111 gms	153 gms	Transmitter = 153 gms Receiver = 116 gms
Barcode	5012739626241	5012739626234	THPW1-CA - 5012739628481 THPW1-CB - 5012739628498 THPW1-CC - 5012739628504 THPW1-CD - 5012739628511 THPW1-CE - 5012739628528
IP Rating	IP20	IP20	IP20
Battery operated	2 x AA (not included) Low battery indicator	2 x AA (not included) Low battery indicator	2 x AA (not included) Low battery indicator
Operating Temperature	Ranges 5°C to 30°C, temperature accuracy +/-0.5°C	Ranges 5°C to 30°C, temperature accuracy +/-0.5°C	Ranges 5°C to 30°C, temperature accuracy +/-0.5°C
Display	Easy to read large LCD display	Easy to read large LCD display	Easy to read large LCD display
Max Load	SPST, volt free, 5A Resistive, 2A Inductive	SPST, volt free, 5A Resistive, 2A Inductive	SPST, volt free, 16A Resistive, 2A Inductive
Range	-	-	Wireless up to 50M
Settings	-	2 x Pre-set & adjustable temp settings (comfort & economy)	5 variants available to overcome interference from nearby properties, or when installing more than one.
Guarantee	1 Year	1 Year	1 Year
Certification & Conformity	BS EN 60730-2-9	BS EN 60730-2-9	BS EN 60730-2-9

**GREEN
BROOK**
ELECTRICAL

Tel +44 (0) 1279 772 772

Fax +44 (0) 1279 422 007

www.greenbrook.co.uk

