

DATA SHEET:

BATC5S / BATC6S

ISSUE: AVJUN19VOL1

230V CCT Microwave Sensor LED Batten



MLA part code	BATC5S	BATC6S
Description	230V 5ft LED CCT Microwave Sensor LED Batten	230V 6ft LED CCT Microwave Sensor LED Batten
Finish	White	
Nett weight (kg)	1.65	1.9
Dimensions (mm)	Length – 1470 Height – 71 Width – 61	Length – 1734 Height – 71 Width – 61
Circuit Wattage (W)	35	40
Lumens (lm)	3000K – 3775 ± 5% 4000K – 4160 ± 5% 6000K – 4160 ± 5%	3000K – 4645 ± 5% 4000K – 5045 ± 5% 6000K – 4955 ± 5%
Efficacy (lm/W)	3000K – 106 4000K – 126 6000K – 117	3000K – 116 4000K – 129 6000K – 123
CCT	3000K - Warm white 4000K - Cool white 6000K - Daylight	
CRI	>80	
Running current (A)	0.15	0.18
Inrush current	40A	
Power factor	0.97	
Beam angle	137°	
Mounting height	3 to 6 meters	
Hold time	5s - 30s - 90s - 3min - 20min - 30min	
Sensor lux settings	2lux - 10lux - 25lux - 50lux - Disable	
Sensor detection angle	360°	
Detection area	25% - 50% - 75% - 100%	
Life span (Hrs)	50,000	
Input voltage	Mains 230V 50Hz	
Construction	Steel & Polycarbonate	
Class	Class I	
IP rating	IP20	
Dimmable	No	
Warranty	5 Years	
Origin of Manufacture	China	
Declaration of Conformity (held on file)	Yes	
Manufactured in accordance with	BS EN 60598	
EAN	5055832999522	5055832999546