Product datasheet Characteristics

GGBGU3424DWSS

Ultimate - Switched Socket 2 USB charger - 2 gang - 13A - stainless steel - white



Main

		≥.	ź
Range	Ultimate		
Aesthetic name	Screwless flat plate		3
Product or component type	Switched socket with USB charger		2
Device presentation	Complete product		מכני
Device application	USB charger		5
Colour tint	Front plate: stainless steel Interior: white		5
Surface finish	Brushed finish		ŝ
Connections - terminals	Screw terminals	<u>;</u>	5
Switch function	2-pole		2
Rated current	13 A at 220240 V AC 50/60 Hz		5

Complementary

Device mounting	Flush	
	Surface	
Outlet standard	BS 1363	
Integrated connection type	2 socket-outlet 220250 V AC 13 A 50/60 Hz 2 USB port 5 V DC 4 A	
Actuator	Rocker	
Number of gangs	2 gangs	
Pilot light	Silver without LED	
Fixing mode	2 screw: M3.5 26 mm diameter: 3.5 mm 2 screw: M3.5 32 mm diameter: 3.5 mm	
Clamping connection capacity	2 x 6 mm² for solid cable(s) 3 x 4 mm² for solid cable(s) 5 x 2.5 mm² for solid cable(s) 3 x 4 mm² for stranded cable(s) 5 x 2.5 mm² for stranded cable(s)	
Socket additional information	Earthed	
Earth circuit	Standard earth	
Material	Stainless steel	
oduct compatibility Mobile/tablet Apple Mobile/tablet Samsung		

	Mobile/tablet LG Mobile/tablet Blackberry Mobile/tablet HTC Mobile/tablet Sony Mobile/tablet Huawei Technologies	
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 1907/2006/EC - REACH directive 2015/863/EU - RoHS directive 2012/19/EU - WEEE directive 2019/1782/EC - ecodesign	
Quality labels	CE	
Quantity per set	Set of 1	
Type of packing	Box	
Type of installation	Indoor	
Depth	30.5 mm	
Width	147.5 mm	
Height	87.5 mm	
Net weight	0.31 kg	

Environment

IP degree of protection	IP20
Standards	BS 1363-2

Contractual warranty

Warranty	18 months	