
Contractor Range - Polished Chrome

Unswitched Spur (13 Amp) - CR934BN



Range Product Victorian Polished Chrome (CR) Insert Type Unswitched Spur (13 Amp) Plate Finish Polished Chrome Switch Colour - Body and Switch Trim Black Height Width Se mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only Standard BS 1363			
Insert Type Plate Finish Polished Chrome Switch Colour Body and Switch Trim Black Height Width Bom Fixing Hole Centres Minimum Box Depth Current Voltage Power Terminal Capacity Farth Terminal Capacity Product Class 1 Ambient Operating Temperature Recommended Location Polished Chrome Polished Chrome Black Box Biack Bom Box Box Fixing = 60.3 mm Box Fixing = 60.3 mm Voltage 25 Undoor use only	Range	Contractor Range	
Plate Finish Switch Colour Body and Switch Trim Black Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Ambient Operating Temperature Recommended Location Face plate must be earthed Indoor use only	Product	Mctorian Polished Chrome (CR)	
Switch Colour Body and Switch Trim Black Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Ambient Operating Temperature Recommended Location Indoor use only	Insert Type	Insert Type Unswitched Spur (13 Amp)	
Body and Switch Trim Black Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Plate Finish	h Polished Chrome	
Height Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Switch Colour	-	
Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Body and Switch Trim	Black	
Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 25 Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Height	86 mm	
Minimum Box Depth Current 13 Amp Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Ambient Operating Temperature Recommended Location Indoor use only	Width	86 mm	
Current Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Fixing Hole Centres	Fixing Hole Centres Box Fixing = 60.3 mm	
Voltage Power Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Minimum Box Depth	25	
Power Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Current	13 Amp	
Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Voltage	230 V	
Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Power	-	
Product Class 1 Face plate must be earthed -5°C - 40°C Recommended Location Indoor use only	Terminal Capacity 4 mm2		
Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Earth Terminal Capacity	5 mm2	
Recommended Location Indoor use only	Product Class 1	lass 1 Face plate must be earthed	
·	Ambient Operating Temperature	e -5°C - 40°C	
Standard BS 1363	Recommended Location	nded Location Indoor use only	
	Standard	BS 1363	

	All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN 9001:2008 Quality System.	It is the policy of the company to continually improve products as part of our development program. Therefore, we respect the right to alter designs and dimensions without prior notice.
	Illustrations and diagrams are produced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing process we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as 01.01.2016. E&OE

British Standards

The Heritage Brass Electrical Collection is designed and manufactured to comply with the requirements of the relevant British Standards. M Marcus Ltd.

Telephone: +44 (0)1384 247 845 Fax 01384 243 312

Email: electsales@m-marcus.com Website: www.m-marcus.com