

DATA SHEET:

LDGL5/ LDGL6/ LDGL9

ISSUE: AVAUG19VOL1

230V IP65 LED Recessed Ground Light 3000K



MLA part code	LDGL5	LDGL6	LDGL9
Description	230V IP65 LED Stainless Steel Recessed Ground Light 3000K		
Finish	Stainless Steel / Die-cast Aluminium		
Nett weight (kg)	0.58	0.74	1.17
Dimensions (mm)	Bezel Diameter – 69 Depth (with sleeve) – 80	Bezel Diameter – 129 Depth (with sleeve) – 70	Bezel Diameter – 160 Depth (with sleeve) – 88
Cut-out (mm)	Without sleeve – 55 With sleeve – 60	Without sleeve – 108 With sleeve – 114	Without sleeve – 138 With sleeve – 144
Wattage (W)	5	6	9
Lumens (lm)	240 ±5%	405 ±5%	610 ±5%
Efficacy (lm/W)	48	68	68
CCT	3000K		
LED Colour	Warm White		
CRI	>80		
Running current (A)	0.04	0.05	0.07
Power factor	0.51	0.53	
Beam angle	50°	95°	100°
Life span (Hrs)	25,000	25,000	25,000
Input voltage	Mains 230V 50Hz		
Construction	Bezel – Stainless steel grade 304 Body – Die-cast aluminium Sleeve – Polycarbonate		
Cable length	2 metres		
Class	Class I		
IP rating	IP65		
Dimmable	No		
Warranty	2 Years		
Origin of Manufacture	China		
Declaration of Conformity (held on file)	Yes		
Manufactured in accordance with	BS EN 60598		
EAN	5056270800364	5056270800388	5056270800418