Aura eco 100

Toilet, en-suite and bathroom ventilation









Key Features

- Axial fan
- Ventilation up to 54 m³/hr
- Slim compact styling
- Quick and easy to fit
- Quiet 29 dB(A)
- Low watt motor 6w
- Low SFP 0.36 W/l/s
- Compatible with 100mm ducting
- IPX4 rating
- 3 year warranty

Aura eco 100

Highly reliable, low energy fan in a modular design for ease of installation and maintenance. The Aura eco 100 is designed to provide quiet extraction in a suitable application.

The fan comes in various control options and is recessed into the wall. The Aura range of fans are slim, compact, attractively styled, are easy to wipe clean and are ideal for through the wall installations.











Models

Basic Control by Remote Switch Timer can be set to run on between 2 and 30 minutes Timer **Humidity Timer** Humidity sensor can be set between 60 - 90% RH


Motion Sensor Timer PIR sensor activates fan




Technical Data


Specification	Aura eco 100B	Aura eco 100T	Aura eco 100HT	Aura eco 100MST
Air flow m³/hr / l/sec	54 / 15	54 / 15	54 / 15	54 / 15
Fan type	Axial	Axial	Axial	Axial
Controls	Basic	Timer	Humidity Timer	Motion Sensor Timer
Mounting	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling
Sound pressure dB(A)@3m	29	29	29	29
Power watts	6	6	6	6
Amps	0.14	0.14	0.14	0.14
Specific Fan Power (SFP)	0.40	0.40	0.40	0.40
Duct diameter (mm)	100	100	100	100
Voltage	230v / 1ph / 50-60Hz			
Rating	IPX4	IPX4	IPX4	IPX4
Material finish	Plastic	Plastic	Plastic	Plastic
Weight (kg)	0.56	0.56	0.56	0.56
Dimensions (H x W x D) mm	150 x 150 x 102			
Part No.	9041347	9041348	9041349	9041350

Dimensions (mm)





-/-1	- 10	1 4 6 6	ice



Model	Α	В	С	D	E
Aura eco 100	150	102	100	122	17

Controls and Accessories

A range of accessories including flexible and rigid ducting kits, controls and grilles are available.

Call: 01494 560800 Visit: airflow.com



E-mail: info@airflow.com Telephone: +44 (0) 1494 525252 Facsimile: +44 (0) 1494 461073

