

Switchsocket Outlets

13 AMP
SURFACE

WITH OUTBOARD
ROCKERS
13 AMP
SURFACE

WITH NEONS
13 AMP
SURFACE

13 AMP SOCKET
20 AMP SWITCH
KEY OPERATED



K2977ALM



K3077WHI



K2945ALM



K2477ALM



K2435ALM



K2977D6ALM



K3046WHI



K2945D6ALM



K2477D6ALM



K5252ALM



K2946ALM



K3045WHI



K2446ALM



K2946D6ALM



K2446D6ALM

- K2977ALM** 5
1 GANG DP WITH
DUAL EARTH TERMINALS
- K2977D5ALM** 1
1 GANG DP WITH DUAL EARTH
TERMINALS WITHOUT BOX
- K2977D6ALM** 1
1 GANG DP WITH RED ROCKER
AND DUAL EARTH TERMINALS
- K2946ALM** 5
2 GANG DP
- K2946D5ALM** 1
2 GANG DP WITHOUT BOX
- K2946D6ALM** 1
2 GANG DP WITH RED ROCKERS

Earth terminal fitted in boxes.

DIMENSIONS:

1 gang: 86 x 86 x 51mm
2 gang: 86 x 146 x 51mm

TERMINAL CAPACITY:

2 x 6 mm² stranded (max)

KNOCKOUTS: 1 gang: 6 x 20mm.

Two in one side and one in each of

the other three sides. One in base

2 gang: 8 x 20mm.

Three in top two in bottom sides and

one in each end. One in base

SPARE BOXES:

1 gang: K829ALM* K899ALM

2 gang: K830ALM* K897ALM

(*without side knockouts)

All boxes have a base knockout.

Boxes: BS 5733: 2010

Socket: BS 1363 Pt.2: 1995

- K3077WHI** 10
1 GANG DP
WITHOUT BOX
- K3046WHI** 5
2 GANG DP
WITHOUT BOX

High integrity earthing

One gang switchsockets, two gang outboard switchsockets and two gang unswitched sockets are fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671: 2008.

Double pole switching

All switchsockets have double pole switching (neutral makes first, breaks last).

- K2945ALM** 5
2 GANG DP
WITH OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS
- K2945D5ALM** 1
2 GANG DP
WITH OUTBOARD
ROCKERS AND DUAL EARTH
TERMINALS WITHOUT BOX
- K2945D6ALM** 1
2 GANG DP
WITH RED OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS
- K3045WHI** 5
2 GANG DP
WITHOUT BOX
WITH OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS

- K2477ALM** 5
1 GANG DP
WITH NEON AND DUAL
EARTH TERMINALS
- K2477D6ALM** 1
1 GANG DP
WITH NEON,
RED ROCKER AND DUAL
EARTH TERMINALS
- K2446ALM** 5
2 GANG DP
WITH NEONS
- K2446D6ALM** 1
2 GANG DP
WITH NEONS
AND RED ROCKERS

- K2435ALM** 5
DP KEY OPERATED SOCKET
- K5252ALM** 5
20AX DP KEY OPERATED SWITCH

Earth terminal fitted in boxes.

DIMENSIONS:

1 gang: 86 x 86 x 51mm

2 gang: 86 x 146 x 51mm

TERMINAL CAPACITY:

1 x 6 mm² stranded (max)

KNOCKOUTS:

1 gang: 6 x 20mm.

Two in one side and one in each of

the other three sides. One in base

2 gang: 8 x 20mm.

Three in top two in bottom sides

and one in each end. One in base

SPARE BOXES:

1 gang: K829ALM* K899ALM

2 gang: K830ALM* K897ALM

(*without side knockouts) All boxes

have a base knockout.

Boxes: BS 5733: 2010

Socket: BS 1363 Pt.2: 1995

Switch: BS EN 60669-1: 1999

ALL UNITS ARE SUPPLIED WITH BACKBOXES (EXCEPT WHI AND D5 PRODUCTS)