

Switchsocket Outlets

13 AMP
SURFACE

WITH OUTBOARD
ROCKERS
13 AMP
SURFACE

WITH NEONS
13 AMP
SURFACE

13 AMP SOCKET
20 AMP SWITCH
KEY OPERATED



K2977ALM



K2977D6ALM



K2946ALM



K2946D6ALM



K3077WHI



K3046WHI



K2945ALM



K2945D6ALM



K3045WHI



K2477ALM



K2477D6ALM



K2446ALM



K2446D6ALM



K2435ALM



K5252ALM

K2977ALM 5
1 GANG DP WITH
DUAL EARTH TERMINALS

K2977D5ALM 1
1 GANG DP WITH DUAL EARTH
TERMINALS WITHOUT BOX

K2977D6ALM 1
1 GANG DP WITH RED ROCKER
AND DUAL EARTH TERMINALS

K2946ALM 5
2 GANG DP

K2946D5ALM 1
2 GANG DP WITHOUT BOX

K2946D6ALM 1
2 GANG DP WITH RED ROCKERS

Earth terminal fitted in boxes.

DIMENSIONS:

1 gang: 86 x 86 x 51mm
2 gang: 86 x 146 x 51mm

TERMINAL CAPACITY:

2 x 6 mm² stranded (max)

KNOCKOUTS: 1 gang: 6 x 20mm.
Two in one side and one in each of
the other three sides. One in base

2 gang: 8 x 20mm.

Three in top two in bottom sides
and one in each end. One in base

SPARE BOXES:

1 gang: K829ALM* K899ALM

2 gang: K830ALM* K897ALM

(*without side knockouts)

All boxes have a base knockout.

Boxes: BS 5733: 2010

Socket: BS 1363 Pt.2: 1995

K3077WHI 10
1 GANG DP
WITHOUT BOX

K3046WHI 5
2 GANG DP
WITHOUT BOX

High integrity earthing

One gang switchsockets, two gang
outboard switchsockets and two
gang unswitched sockets are fitted
with two earth terminals to provide
a double earth facility for use when
installations require a high integrity
protective connection as specified
within BS 7671: 2008.

Double pole switching

All switchsockets have double pole
switching (neutral makes first,
breaks last).

K2945ALM 5
2 GANG DP
WITH OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS

K2945D5ALM 1
2 GANG DP
WITH OUTBOARD
ROCKERS AND DUAL EARTH
TERMINALS WITHOUT BOX

K2945D6ALM 1
2 GANG DP
WITH RED OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS

K3045WHI 5
2 GANG DP
WITHOUT BOX
WITH OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS

K2477ALM 5
1 GANG DP
WITH NEON AND DUAL
EARTH TERMINALS

K2477D6ALM 1
1 GANG DP
WITH NEON,
RED ROCKER AND DUAL
EARTH TERMINALS

K2446ALM 5
2 GANG DP
WITH NEONS

K2446D6ALM 1
2 GANG DP
WITH NEONS
AND RED ROCKERS

K2435ALM 5
DP KEY OPERATED SOCKET

K5252ALM 5
20AX DP KEY OPERATED SWITCH

Earth terminal fitted in boxes.

DIMENSIONS:

1 gang: 86 x 86 x 51mm

2 gang: 86 x 146 x 51mm

TERMINAL CAPACITY:

1 x 6 mm² stranded (max)

KNOCKOUTS:

1 gang: 6 x 20mm.

Two in one side and one in each of
the other three sides. One in base

2 gang: 8 x 20mm.

Three in top two in bottom sides
and one in each end. One in base

SPARE BOXES:

1 gang: K829ALM* K899ALM

2 gang: K830ALM* K897ALM

(*without side knockouts) All boxes
have a base knockout.

Boxes: BS 5733: 2010

Socket: BS 1363 Pt.2: 1995

Switch: BS EN 60669-1: 1999

ALL UNITS ARE SUPPLIED WITH BACKBOXES (EXCEPT WHI AND D5 PRODUCTS)