


Clarity Perspex Range - Clear Perspex

3 Gang LED Dimmer - PPX.580.LED-WH



Range	Clarity Perspex Range	
Product	Clarity Perspex	
Insert Type 3 Gang LED Dimmer		
Plate Finish	Plate Finish Clear Perspex	
Switch Colour White		
Body and Switch Trim	White	
Height	88 mm	
Width	148 mm	
Fixing Hole Centres	Fixing Hole Centres Box Fixing = 120.6 mm	
Minimum Box Depth	th 35	
Current -		
Voltage 230 V		
Power	Max 120 W - 10 Lamps Trailing Edge	
Terminal Capacity 4 mm2		
Earth Terminal Capacity	Earth Terminal Capacity 5 mm2	
Product Class 1	Class 1 Face plate must be earthed	
Ambient Operating Temperature	Ambient Operating Temperature -5°C - 40°C	
Recommended Location	mmended Location Indoor use only	
Standard	BS EN 55014, BS EN 60669-2-1	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN 9001:2008 Quality System.	It is the policy of the company to continually improve products as part of our development program. Therefore, we respect the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are produced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing process we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as 01.01.2016. E&OE



British Standards
The Heritage Brass Electrical
Collection is designed

Collection is designed Collection is designed and manufactured to comply with the requirements of the relevant British Standards.





M. Marcus Ltd. Telephone: +44 (0)1384 247 845 Fax: 01384 243 312 Email: electsales@m-marcus.com m.marcus Website: www.m-marcus.com